













1D & 2D Dual

Interface

DPM

Laser aimer

Acuscan

Megapixel



IP64



drop







Warranty 5 Years



Features

New Vision

The NVH300 Angler DP is the first of Newland's New vision barcode readers designed for high-end and specialist scanning requirements that include an element or combination of; industrial protection, High density and DPM code reading acumen.

DPM Decoding

With a new generation of industrial decoding, the NVH300 Angler DP can read laser marked and dot peened barcodes on many types of surfaces. Surgical equipment, machinal engineering parts and printed circuit boards

Advanced illumination

The NVH300 Angler DP uses three different light sources to combat the contrast variances encountered from different materials marked by the DPM codes. The issues confronted by the reflection and distortion of barcodes can be negated by using different colored light projected from different angles.

Intelligent Configuration

The NVH300 Angler DP uses the three illumination colors it has and the angles of the light source with a level of intelligence by cycling through the options automatically after a short delay in attempting to scan a code. When the ideal light colors and angle combination is found, the NVH300 remembers the last setting for the following code.

Nset

Newlands's new vision range of scanners is accompanied by its own advanced configuration software. Nset is a more DPM and High-density feature-packed version of our Easyset configuration software.

Industrial Design

The NVH300 Angler DP is fortified inside and out. With an IP64 sealed housing and 1.8m drop specification, the NVH300 DPM is Newland's most formidable handheld scanner. Dirty, harsh environments are no deterrent to the NVH300 DPM. We back this up with a standard 5 Year warranty.





Suggested industries









Logistics

Manufacturing

NVH300 Angler DP Technical specifications

1D All major 1D symbologies, including EAN 8, EAN 13, UPC E, UPC A, Code128, Coupon, UCC/EAN128,

CodaBar, I2Of5, Febraban, ITF14, ITF6, Matrix 25, Code39, Code93, ISSN, ISBN, Industrial 25,

Standard 25, China Post 25, Plessey, Code 11, MSI Plessey, UCC/EAN Composite, GS1 Databar, Code

49, Code 16K, AIM 128, ISBT 128.

2D All major 2D symbologies, including QR Code, Data Matrix.

Image Sensor 1280x960 CMOS

Aiming 650nm laser diode

Illumination Direct: White LED; Diffuse: Ring of red LEDs, Ring of blue LEDs

Depth of Field Code 39 (5mil) 18mm-90mm

Depth of Field DataMatrix (10mil) 0mm-90mm

Depth of Field QR (15mil) 0mm-90mm

Field of View Horizontal 41°

Field of View Vertical 31°

Scan Angle Roll ±60°

Scan Angle Roll 360°

Scan Angle Skew ±55°

Motion Tolerance Max 2m/s (6.56ft/s)

Minimal Print Contrast 20%

Physical

Current @ 5VDC Operating 450mA (typical), 475mA (max)

Dimensions (mm) 76(W) x 107(D) x 185(H) mm

Input Voltage 5VDC±5%

Interfaces RS-232, USB

Notifications Beep, LED indicator, vibration

Power Consumption 2250mW (typical)

Weight 245g

Environmental

Operating Temperature -20°C to 50°C (14°F to 122°F)

Storage Temperature -40°C to 70°C (-40°F to 158°F)

Electro Static Discharge (ESD) ±8 KV (direct discharge); ±16 KV (air discharge)

Drop 1.8m

IP Rating IP64

Software

Humidity

Configuration Tools NSet

Certifications

Hardware FCC Part 15 Class B, CE EMC Class B

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

5% to 95% (non-condensing)

© Newland EMEA 2023, all rights reserved



NVH300 Angler DP Technical specifications

Warranty

Standard 5 years

