



1D







LED aimer



;;; ⟨ **CMOS IP42** 

1.2M drop



EasySet



Warranty 3 Years



**BS80 Piranha II 1D** 

Handheld Scanners

## **Features**

## **Superior 1D Reading Performance**

Equipped with a snappy 1D engine, the BS80 Piranha II can read all major 1D symbologies from both paper and screen.

### **Easy Bluetooth Pairing**

With Bluetooth 4.0 wireless technology, the BS80 Piranha II enables effortless pairing to any Android, iOS, or Windows device, making it simple and convenient for users to transmit data.

## Seamless Barcode Capture and Storage

The BS80 Piranha II offers versatile barcode scanning capabilities, enabling fast real-time scanning with seamless data transfer to the host via Bluetooth. However, users can also take advantage of the 1MB memory when operating in batch collection mode, which can store thousands of barcodes offline for subsequent download via Bluetooth or cable.

## Edits On the Go

The BS80 Piranha II boasts not only a reliable scan button but also two extra

buttons for convenient data editing. For data collection mode, the Delete button allows users to quickly rectify scanning errors by deleting the last scanned barcode. Meanwhile, the Function button serves as a virtual keyboard recall feature, enabling manual data input on a wide range of host devices, including iOS products. This makes the BS80 Piranha II an ideal companion for all your data collection needs.

### **Versatile Charging & Communication**

The BS80 Piranha II features a fast and reliable USB-C port that can be used both for charging and establishing a connection to a host to download data or access the EasySet configuration software. In addition, the device also supports the use of pogo pins to charge via the cradle.

## Multi-Device Charging

The BS80 Piranha II offers an optional two-bay charging solution that can be easily linked together to create a multi-charging station. With optimized charging capabilities, users can daisy-chain up to five cradles, allowing them

to charge up to ten scanners simultaneously using a single power supply.





# Suggested industries









Hospitality



Retail

# BS80 Piranha II 1D Technical specifications

Date	_ ^		
Dal	21 L	.a. (0)	ше

All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, ISSN, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, etc.

Image Sensor 2500 Linear Imager

Depth of Field EAN 13 (13mil) 55-550mm

Depth of Field Code 39 (5mil) 70-185mm

Scan Angle Pitch: ±60°; Skew: ±60°

Minimal Print Contrast 25%

Depth of Field Code 128 (10mil)

### **Physical**

Battery Type 3.7V 900mAh rechargeable Li-ion battery

Current Operating/Standby 185mA (Bluetooth is on)/25mA

Dimensions (mm) 88.0(L) × 46.0(W) × 24.5(H) mm

Expected Battery Life 6.5 hours of continuous operation (scan once per 6s)

60-500mm

Interfaces Type-C USB, Bluetooth HID/SPP/BLE profiles

Notifications Beep, LED and vibration

Weight 67g

#### Wireless

Wireless Standards 2.4 - 2.5GHz ISM band, compatible with Bluetooth 4.0/3.0/2.1+EDR

Bluetooth Transmission Range 50m (open space)

## **Environmental**

Operating Temperature -20°C to 50°C (-4°F to 122°F)

Storage Temperature -40°C to 70°C (-40°F to 158°F)

Charge Temperature 0°C to 45°C (32°F to 113°F)

Humidity 5%~95% (non-condensing)

Electro Static Discharge (ESD) ±4 KV (direct discharge); ±12 KV (air discharge)

Drop 1.2m

IP Rating IP42

#### Software

Configuration Tools EasySet

### Certifications

Hardware CE RED, CE UK, FCC, TELEC, IEC 62471, RoHS, IEC60825

## Warranty

Standard 3 years

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

