



1D & 2D



Dual  
Interface



Mobile  
Reading



CMOS



Chip



EasySet



Warranty  
2 Years



## FM3051 Grouper

Stationary Scanners

## Features

### Superior decoding performance.

Your employees can scan virtually any barcode, including 1D and 2D, at an extraordinary speed.

### Effortless scanning from mobile phone screen.

Built to read from an LCD screen, the FM3051 Grouper can easily read barcodes from any mobile device screen. An extended capability of IR reading allows the device to detect barcodes under virtually any ambient light. Whether you operate at daytime or nighttime, scanning is quick and efficient.

### Easily mounted in small spaces.

The FM3051 Grouper is designed for businesses that require high performance and a minimal footprint. With its

small size, the device is ideal for kiosk integration and other POS solutions.

### Easy to install.

The FM3051 Grouper can be set up quickly and easily. A plug-and-play simplicity enhances your experience right from the start. The device can be further configured according to your needs by using a simple barcode programming guide.

### Application scenarios.

POS Solutions, kiosk integration, scanning from a mobile phone screen, such as for loyalty programs or ticket validation.

## Suggested industries



Entertainment



Finance



Hospitality



Retail



Transportation

# FM3051 Grouper Technical specifications

## Performance

Image Sensor	CMOS 752*480
Processor	0390 Chip+MCU
Illumination	White LED
Minimal Print Contrast	25%
Scan Angle Roll	360°
Scan Angle Pitch	±40°
Scan Angle Skew	±40°
Field of View Horizontal	75°
Field of View Vertical	50°
Scan Modes	Sense Mode, Continuous Mode
Scan Rate	60 frames per second
Scan Window	38.3mm×60.4mm

## Data Capture

1D	All major 1D symbologies including EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128 (FNC1, FNC2, FNC3), Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar (RSS-Expand, RSS-Limited, RSS-14), Code 39, Code 11, MSI-Plessey, Plessey
2D	All major 2D symbologies including DF417, Data Matrix, QR Code, Chinese Sensible Code.

## Physical

Dimensions (mm)	78.7(W)×67.7(D)×62.5(H)mm (max.)
Weight	195g
Material	PBT, ABS, Aluminium
Interfaces	RS-232, USB
Notifications	Beep
Input Voltage	5VDC±5%
Current @ 5VDC Operating	108mA (typical), 114mA (max.)
Power Consumption	534mW (typical)
Power Supply Input	DC5V, 1.5A
Power Supply Output	AC100~240V, 50~60Hz

## Environmental

Operating Temperature	-20°C to 60°C (-4°F to 140°F)
Storage Temperature	-40°C to 70°C (-4°F to 158°F)
Humidity	5%~95% (non-condensing)
Electro Static Discharge (ESD)	±8 KV (air discharge); ±4 KV (direct discharge)

## Accessories

Standard	USB Cable
Optional	RS232 Cable, Adapter

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved

# FM3051 Grouper Technical specifications

Software	
Configuration Tools	EasySet
Certifications	
Hardware	FCC Part15 Class B, CE EMC Class B,KC
Warranty	
Standard	2 years